



## Macchina della Luce I

pendant lamp

materials and colours

made of diffuser discs lined with gold or copper coloured leaf (brass rods) or silver coloured leaf (nickel rods), nickel base (dimmable versions) or grey matt base (not dimmable version).

light source

bulb: halogen bi-pin 12V

GY6,35 [ max 1x90W - inclusa 60W ]

GY6,35 [ max 1x75W - inclusa 50W ]

energy class from B to E

[ energy class B ]

or

LED: low voltage 24V DC LED board [ 5x6W ]

[ class included A ]

power supply

halogen: 220-240V (110V available on request) - transformer toroidal 200W (not dimmable) or electronic 200W (dimmable with pure trailing edge phase dimmers only - IGBT)

LED: 220-240V - driver 24V DC Triac dimmable (available on request 1...10V or DALI).

dimensions

discs Ø 80 cm, 50 cm, 30 cm with flat leaf,

base for dimmable versions Ø 21x10,5 H cm,

base for not dimmable version Ø 14x13 H cm,

rods H 145 cm variable (available on request 300 cm),

weight 8 kg.

order code

MI / halogen / gold / not dimmable

MIAG / halogen / silver / not dimmable

MIR / halogen / copper / not dimmable

MIEL / halogen / gold / dimmable

MIELAG / halogen / silver / dimmable

MIELR / halogen / copper / dimmable

MILD / LED / gold / dimmable

MILDAG / LED / silver / dimmable

MILDR / LED / copper / dimmable