



**shot** Design: Sebastian David Büscher

für festen Untergrund

for solid ground

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Sicherheitsglas klar

light technology:  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h

material:  
aluminium die-casting  
powder-coated  
safety glass clear

Flood Reflektor symmetrisch

inkl. Alu-Ring lose, ø 80 mm

flood reflector symmetric

incl. aluminium ring loose, ø80 mm

dimmbar

**Schutzart:**  
IP65

dimmable

protection class:  
IP65

**Anschluss:**  
5 m Zuleitung  
(H05RN-F 3G0,75) inkl. Schutz-  
kontaktstecker anschlussfertig

**EEK:**  
A+


connection:  
5 m supply cable  
(H05RN-F 3G0,75) incl. safety  
plug ready to connect

EEC:  
A+

ortsveränderlich

movable

**shot 4 W**



**Art.-Nr.**  
item no.

**Farbe**  
colour

**Systemleistung**  
system performance

**Lichtrichtung**  
light direction

91090-4W-AN

anthracite  
RAL 7016

4 W/260 lm



91090-4W-CB

cool brown

4 W/260 lm




91090-4W-BL

deep black  
RAL 9005

4 W/260 lm



**shot 15 W**



91090-15W-AN

anthracite  
RAL 7016

15 W/980 lm



91090-15W-CB

cool brown

15 W/980 lm



91090-15W-BL

deep black  
RAL 9005

15 W/980 lm



Größe in mm  
size in mm

+ Anschluss optional mit IP44.de connect. Produktdetails auf IP44.de.  
connection with IP44.de connect as an option. product details on IP44.de.