

# URINALS

## Siphonic urinal ANTERO 84115.3



### TECHNICAL DATA

Order no.	84115.3	Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89009.7
Certified to	EN 80, EN 13407		LIS SMART CONTROL-U horizontal inlet connection, order no. 89418.9
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4 LIS SMART CONTROL-U, order no. 37066.0		1-liter spare part siphon, order no. 89313.6 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Specification	1-l flushing siphonic urinal Ceramic siphon cover Siphon replaceable from top without dismantling urinal Only in combination with fixing set, order no. 89282.6 Charge 000 – DN 40 Charge 401 – DN 50	Colours	see colour table
Water inlet	concealed 1/2"	<b>SPECIFICATION TEXT</b>	
Outlet	horizontal (variable 60 mm)	Siphonic urinal Laufen-ANTERO, sanitary ceramic	
Flushing	minimum 0.5 l - 3.0 l	EN 80, EN 13407, dimensions 380 x 365 x 770 mm	
Flushing rate	minimum 0.3 l/s	minimum 0.5 l - 3.0 l flush, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal (variable 60 mm), flushing rate minimum 0.3 l/s	
Weight	25,0 kg	siphon replaceable from top without dismantling urinal,	
Mounting acc. incl.	Ceramic siphon cover, order no. 89213.0 laufen EasyFit system M8, order no. 89282.6 Charge 000 – 1-liter siphon with waste connection pipe DN 40 Charge 401 – 1-liter siphon with waste connection pipe DN 50	Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)	
		Further options / accessories: LIS horizontal inlet connection, 1-liter spare part siphon, LIS CU2 concealed frame for urinal without integrated control or LIS SMART CONTROL-U concealed kit for urinal flash control and front plate with infrared sensor	
		Order no. 84115.3	

### TECHNICAL DRAWINGS / S 1 : 20

