


Dau Spot



Milan



#### Dau 80 F CC.

Ø80 x 80 mm | H. 184 mm

1 x COB LED 

956 lumens | 2.700K | CRI 90

3-step MacAdam

Driver CC included

Dimmable leading and trailing edge

10-100%

PF. 0,90

Ripple < 10%

Class I: Basic insulation

#### Finishes

- 6880 ● Brushed aluminium
- 6881 ● Matt white lacquering (RAL 9016)
- 6882 ● Black satin aluminium

#### DOWNLOADS

##### Catalogue

[6880/6881/6882](#)

##### 3D Files

[6880](#)

[6881](#)

[6882](#)

##### 3D Max Files

[6880](#)

[6881](#)

[6882](#)

##### Assembly instructions

[6880/6881/6882](#)

##### Photometric curve

[6880/6881/6882](#)


##### Economic efficiency index

[6880/6881/6882](#)

Pure geometry.


Dimable version in DALI system or 1-10 V on request. Extruded aluminium outer body. Finishes in anodised brushed aluminium, white lacquer (RAL 9016) and satin brushed aluminium in black. Injected aluminium LED


support and heat sink. Finishes in mat metallic grey (similar to RAL 9006), white lacquer (RAL 9016) and satin black (RAL 9005). Inner bodies: injected aluminium base mount.



#### Dau 80 F GU10 W.

Ø80 x 80 mm | H. 184 mm  
1 x GU10 Bulb retrofit

Led 8W Ø63mm   
Code 2053 | CRI 80  
720 lumens | 2.700K

Led 8W Ø50mm   
Code 2123 | CRI 80  
700 lumens | 2.700K  
Dimmable

Class I: Basic insulation

#### Finishes

- 6028 ● Brushed aluminium
- 4028 ● Matt white lacquering (RAL 9016)
- 1028 ● Black satin aluminium

Extruded aluminium outer body. Finishes in anodised brushed aluminium, white lacquer (RAL 9016) and satin brushed aluminium in black.

Decorative cover, lampshade in injected polycarbonate. Finishes in metallic grey lacquer (similar to RAL 9006), white lacquer (RAL 9016) and

black lacquer (RAL 9005). Inner bodies: injected aluminium base mount

#### DOWNLOADS

##### Catalogue

[6028/4028/1028](#)

##### 3D Files

[6028](#)  
[4028](#)  
[1028](#)

##### 3D Max Files

[6028](#)  
[4028](#)  
[1028](#)

##### Assembly instructions



[6028/4028/1028](#)

##### Photometric curve


[6028/4028/1028](#)

##### Economic efficiency index

[6028/4028/1028](#)




#### Dau 80 F 1P CC T.

Ø80 x 80 mm | H. 165 mm  
 1 x COB LED   
 956 lumens | 2.700K | CRI 90  
 3-step MacAdam  
 Driver CC included  
 Dimmable leading and trailing edge  
 10-100%  
 PF. 0,90  
 Ripple < 10%  
 Class I: Basic insulation  
 One-phase adapter

#### Finishes

- 6886 ● Brushed aluminium
- 6887 ● Matt white lacquering (RAL 9016)
- 6888 ● Black satin aluminium

#### Dau 80 F 3P CC T.

Ø80 x 80 mm | H. 165 mm  
 1 x COB LED   
 956 lumens | 2.700K | CRI 90  
 3-step MacAdam  
 Driver CC included  
 Dimmable leading and trailing edge  
 10-100%  
 PF. 0,90  
 Ripple < 10%  
 Class I: Basic insulation  
 Three-phase adapter

#### Finishes

- 6889 ● Brushed aluminium
- 6890 ● Matt white lacquering (RAL 9016)
- 6891 ● Black satin aluminium

#### DOWNLOADS

##### Catalogue

[6886/6887/6888](#)  
[6889/6890/6891](#)

##### 3D Files

[6886](#)      [6889](#)  
[6887](#)      [6890](#)  
[6888](#)      [6891](#)

##### 3D Max Files

[6886](#)      [6889](#)  
[6887](#)      [6890](#)  
[6888](#)      [6891](#)

##### Photometric curve

[6886/6887/6888](#)  
[6889/6890/6891](#)



##### Economic efficiency index

[6886/6887/6888](#)  
[6889/6890/6891](#)

Dimmable version in DALI system or 1-10 V on request. Extruded aluminium outer body. Finishes in anodised brushed aluminium, white lacquer (RAL 9016)


and satin brushed aluminium in black. Injected aluminium LED support and heat sink. Finishes in mat metallic grey (similar to RAL 9006), white lacquer


(RAL 9016) and satin black (RAL 9005). Inner bodies: injected aluminium base mount.



#### Dau 80 F 1P GU10 T.

Ø80 x 80 mm | H. 162 mm  
1 x GU10 Bulb retrofit

Led 8W Ø63mm   
Code 2053 | CRI 80  
720 lumens | 2.700K

Led 8W Ø50mm   
Code 2123 | CRI 80  
700 lumens | 2.700K  
Dimmable


Class I: Basic insulation  
One-phase adapter


#### Finishes

- 3163 ● Brushed aluminium
- 1164 ● Matt white lacquering (RAL 9016)
- 5164 ● Black satin aluminium

#### Dau 80 F 3P GU10 T.

Ø80 x 80 mm | H. 162 mm  
1 x GU10 Bulb retrofit

Led 8W Ø63mm   
Code 2053 | CRI 80  
720 lumens | 2.700K

Led 8W Ø50mm   
Code 2123 | CRI 80  
700 lumens | 2.700K  
Dimmable

Class I: Basic insulation  
Three-phase adapter

#### Finishes

- 6163 ● Brushed aluminium
- 4164 ● Matt white lacquering (RAL 9016)
- 6164 ● Black satin aluminium

## DOWNLOADS

### Catalogue

[3163/1164/5164](#)  
[6163/4164/6164](#)

### 3D Files

[3163](#)      [6163](#)  
[1164](#)      [4164](#)  
[5164](#)      [6164](#)

### 3D Max Files

[3163](#)      [6163](#)  
[1164](#)      [4164](#)  
[5164](#)      [6164](#)

### Photometric curve

[3163/1164/5164](#)  
[6163/4164/6164](#)

### Economic efficiency index

[3163/1164/5164](#)  
[6163/4164/6164](#)

Extruded aluminium outer body.  
Finishes in anodised brushed aluminium, white lacquer (RAL 9016) and satin brushed aluminium in black.

Decorative cover, lampshade in injected polycarbonate. Finishes in metallic grey lacquer (similar to RAL 9006), white lacquer (RAL 9016) and

black lacquer (RAL 9005) Inner bodies: injected aluminium base mount.